



KONICA MINOLTA

AccurioShine
3600

LUXURY AT YOUR FINGERTIPS

RETHINK 3D GLOSS & FOIL WITH
DIGITAL SPOT UV COATING



Giving Shape to Ideas

TECHNICAL SPECIFICATIONS

AccurioShine 3600

Printing technology	<ul style="list-style-type: none"> – Konica Minolta's exclusive inkjet engine technology – Drop-on-Demand (DoD) technology – Piezoelectric printheads, developed and manufactured by Konica Minolta – Single-pass printing – Flexible printing architecture
Coating thickness	Depending on your file, the inks used and the type of surface of your sheet, the coating thickness can vary <ul style="list-style-type: none"> – Laminated and aqueous coating: 21 µm – 116 µm for 3D-raised effects and tactile finish – Toner and coated paper: 30 µm – 116 µm for 3D-raised effects and a tactile finish – Lowest possible thickness using dithering mode: 7 µm (substrate permitting)
Production speed	<ul style="list-style-type: none"> – 2D/flat mode: Up to 2,077 A3 sheets per hour (with 21 µm) – 3D/raised mode: Up to 1,260 A3 sheets per hour (with 51 µm) – Up to 547 A3 sheets per hour (with 116 µm)
Registration	Uses the Artificial Intelligence SmartScanner® for full real-time automated sheet-to-sheet registration process; no crop marks required, registration accuracy to ± 200 µm
Formats	Min.: 21 x 29.7 cm (8" x 11.8") Max.: 36.4 x 75 cm (14.3" x 29.5") Max. printable width: 35.2 cm (13.9")
Substrate thickness	Min.: 135 g/m² and not less than 150 µm before printing and lamination Max.: 450 g/m² and not more than 450 µm before printing and lamination Motorized height-adjustment printheads
Substrates	<ul style="list-style-type: none"> – Printing on most matte or glossy laminated surfaces, with or without aqueous coating, layered paper, plastic, PVC and other coated materials – Printing directly on most digital prints with no lamination or coating required
UV coatings and capacity	10 litres (2.6 gal.) tank capacity
High-capacity automatic paper feeder	<ul style="list-style-type: none"> – Vacuum belt feeding system – Able to handle a paper pile up to ± 28 cm (11") approximately 2,250 sheets at 135 g/m² – All paper formats from A4 up to 36.4 x 75 cm (14.3" x 29.5")
Paper exit tray	Tray able to handle a paper pile: <ul style="list-style-type: none"> – Up to 15 cm (5.9") approximately 1,250 sheets at 135 g/m² – Approximately 1,250 sheets at 135 g/m² – All paper formats from Letter up to 36.4 x 75 cm (14.3" x 29.5") – No paper extensions available – Automatic tray full sensor

iFoil One (Option)

Formats	Min.: 21 x 29.7 cm (8" x 11.8") Max.: 36.4 x 75 cm (14.3" x 29.5") When using the latest upgrade kit Exit Motor Roller V4
Supported varnish thickness	Min.: 36 µm Max.: 116 µm
Substrate types	<ul style="list-style-type: none"> – Coated paper (best) – Matte or gloss laminated surfaces – Surfaces with or without aqueous coating – Surfaces with or without lamination film – Layered paper
Average foiling speed	30 meter per minute
Number of areas per sheet	Up to 3 stamp areas per SRA3 sheet Up to 5 stamp areas per 75 cm sheet (minimum separation distance 10 cm)
Foil specifications	<ul style="list-style-type: none"> – Standard foil core: 1 inch (braking system) – Foil length: Max. 400 m (do not exceed) – Foil width (roll width): Min. & Max. 320 mm

Paper path	<ul style="list-style-type: none"> – 100% flat paper path – Vacuum-feed system – Air-feed system – Automatic double-sheet detection – In-line LED dryer – On-the-fly drying and curing via integrated LED dryer
Maintenance and remote technical support	<ul style="list-style-type: none"> – Daily maintenance completed in less than 10 minutes – Majority of procedures are automated – Automatic cleaning system – From cold start to production in less than 10 minutes – Remote troubleshooting & support via included video/web camera (high-speed Internet connection required)
Pilot panel	Integrated user-friendly LCD touchscreen
Options	<ul style="list-style-type: none"> – iFoil One – Automatic PDF File Converter (using RIP PC-C1) – VDP barcode scanner – Artificial Intelligence SmartScanner® lighting for metalized substrates – Corona Treatment System (CTS) – Ozone filter (only available when CTS option is also fitted)
Dimensions (L x W x H)	4.02 x 1.20 x 1.80 m (13.19' x 3.94' x 5.91') Necessary clearance: 1 m (3.3') on all 4 sides
Weight	± 1,068 kg (2,355 lb)
Electrical requirements	<ul style="list-style-type: none"> – For Europe and the majority of the world: 7.5 kW (32 A) at 220-240 Volts 50/60 Hz -2 plugs CEE/IP44 32A (1P+N+PE) – For USA/Canada only: 7.5 kW (30A) at 208-240 Volts 50/60 Hz -2 Nema plugs L6-30P (30A 250V, 2P 3 Wires)
Operating requirements	Temperature: 18°C – 30°C (64°F – 86°F) Environment relative humidity: 30 – 50% (no condensation) Optimum: 22°C (72°F), 40% humidity
Average yearly duty cycle	±600,000 pages in 36 x 52 cm format
Respecting the environment	<ul style="list-style-type: none"> – Eliminates resource waste (wasted electricity, paper and varnish) – No plates (offset) or screens (screen printing) – No cleanup or preparation between jobs – Drastic reduction in consumables and use of bulk packaging – Coating without volatile solvent

Foil processing temperature	110°C is the default setting for M Series Foils Min.: 80°C Max.: 130°C
Paper exit tray	AccurioShine 3600 paper exit tray (PET) will be refitted to iFoil One upon installation Max. height: 15 cm (5.9") approximately 1,250 sheets at 135 g/m²
Interface	Easy-to-use settings through JVTI software
Footprint (iFoil One alone)	Length: 138 cm (with PET: 183 cm) Width: 124 cm Weight: 504 kg
Electrical requirements	2 plugs CEE 17 IP44 32A (32A 250V, 1P+N+PE)

The default sheet format is A3, unless otherwise stated:
 1) with an additional option installed
 2) speed will vary according to printing parameter used
 3) confirm substrate/toner compatibility with Konica Minolta



For Plastic Waste Management Details



For Battery Waste Management Details

Konica Minolta Business Solutions India Pvt. Ltd.

Building No: 8, Tower-C, 10th Floor, DLF Cyber City, Phase-2, Gurugram, Haryana-122002, India
 Toll Free No. 1800 2662525 | URL: www.konicaminolta.com | marcom@bin.konicaminolta.in

Connect with us: