

AccurioPress C84hc / C74hc General Specifications

| Main Unit | C84hc | C74hc |
|---|---|-------------------------------------|
| Type | Console type | |
| Colour support | Full colour | |
| Writing resolution | Equivalent to 3600 dpi x 2400 dpi | |
| Gradation | 8 bit / 256 gradation | |
| Warm-up time | 390 sec. or less | |
| Magnification | 25 - 400%, in 0.1% steps | |
| Print speed full colour & monochrome | 81 ppm (A4 Landscape) / 45 ppm (A3) | 71 ppm (A4 Landscape) / 39 ppm (A3) |
| First Copy/Printing Time (Color/Monochrome) | 6.1 seconds or less/4.0 seconds or less | |
| Paper size | 100 x 148 - 330.2 x 487.7 mm (up to 1,300 mm with optional Banner Kit) | |
| Paper weight | 62 - 360 gsm | |
| Paper capacity | 15,390 sheets (with main body standard tray + 3 paper feeding units (PF-707m Type C)) | |
| Paper weight | 12,000 sheets (with Large Capacity Stacker LS-507 x 2) | |
| Controller CPU | Intel Core i5-6500 3.2GHz ¹ | |
| Power supply | AC 200V, 25A, 50Hz/60Hz (Voltage to ground 100V) | |
| Maximum Power Consumption | 5,760W | |

| Main Unit Size (WxDxH mm) | Main unit | 31.50 x 35.55 x 40.98 inches (800 x 903 x 1,041 mm) |
|---------------------------|-----------------------------|---|
| | (Recommended) configuration | 84.65 x 35.55 x 58.19 inches (2,150 x 903 x 1478 mm) (main unit + LU-202m + FS-532m) |

| | |
|------------------|----------------------------|
| Main Unit Weight | Approx. 672.41 lb (305 kg) |
|------------------|----------------------------|

| | |
|--------------------|---|
| Maximum Print Area | 12.72 x 18.90 inches (323 x 480 mm) (Banner sheet: 12.72 x 50.98 inches (323 x 1,295 mm)) |
|--------------------|---|

| Compatible Paper weights | Main unit | 16 to 68 lb (62 to 256 ² g/m ²) |
|--------------------------|--------------|--|
| | Paper feed | PF-707m: 16 to 95 lb (62 to 360 g/m ²) MB-508: 16 to 81 lb (62 to 300 g/m ²) |
| | Paper output | Straight paper output: 16 to 95 lb (62 to 360 g/m ²) Reverse double-sided output: 16 to 95 lb (62 to 360 g/m ²) |
| | Banner paper | MK-760/MK-761: 34 to 68 lb (128 to 256 g/m ²) (up to 51.18 inches (1,300 mm) length) LU-202XLm: 34 to 68 lb (128 to 256 g/m ²) (18.85 to 30.00 inches (478.8 to 762 mm) length) |

| | |
|---|---|
| Paper Feed Capacity (21 lb (80 g/m ² sheet)) | PF-707m: 3-level tray, air suction system Top level/Middle level: 1,390 sheets each, Bottom level: 1,850 sheets 15,390 sheets (Main unit tray, with 3 PF units connected) |
| Paper output capacity (21 lb (80 g/m ² sheet)) | RU-518m (Sub Tray) 100 sheets (stacking height: 20 mm) |

| Copy Speed | Single side A4 | 81 ppm or 4,399 sides or more/hour | 71 ppm or 3,848 sides or more/hour |
|------------|----------------|------------------------------------|------------------------------------|
| | Simplex A3 | 45 ppm or 2,404 pph | 39 ppm/ 2,074 pph |

| | |
|------------------------|---|
| Compatible Controllers | IC-609 (KM), IC-317 ver.3.0 (Fiery), IC-419 ver.3.0 (Fiery) |
|------------------------|---|

*1: In the case of Image Controller IC-609

*2: For 58 to 68 lb (217 to 256 g/m²), only papers that are at least 8.27 to 11 inches (210 x 279.4 mm)

Other options

| | |
|--------------------------|---------|
| Working Table | WT-511 |
| Envelope Fusing Unit | EF-107 |
| Dehumidifier Heater | HT-511 |
| Status indicator light | MK-744C |
| Intelligent Media Sensor | IM-101 |

- All specifications refer to A4-size paper of 80 gsm quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



KONICA MINOLTA

Konica Minolta Business Solutions India Pvt. Ltd.

Building No: 8, Tower-C, 10th Floor, DLF Cyber City, Phase-2, Gurugram, Haryana-122002, India
Board No. +91-124-6652000 | URL: bt.konicaminolta.in | marcom@bin.konicaminolta.in

Connect with us :

Toll Free No. for Demo: 1800-266-2525

Paper feeding options

| | |
|---|-----------|
| Paper Feeder Unit | PF-602m |
| Dehumidifier Heater (Europa) | HT-504 |
| Dehumidifier Heater (Japan/North America) | HT-505 |
| Paper Feed Unit | PF-707m |
| Dehumidifier Heater | HT-506 |
| Feed Adjuster | FA-502 |
| Multi Bypass Tray | MB-508 |
| Large Capacity Unit | LU-202m |
| Large Capacity Unit | LU-202XLm |
| Dehumidifier Heater | HT-503 |
| Dehumidifier Heater | HT-515 |
| Mount Kit | MK-746 |
| Multi Bypass Tray | MB-509 |
| Banner Tray Unit (Input) | MK-760 |

Paper ejection options

| | |
|---|---------|
| Finisher | FS-532m |
| Saddle Stitcher | SD-510 |
| Punch Unit | PK-525 |
| Mount Kit | MK-732 |
| Post Inserter | PI-502 |
| Saddle Stitcher | SD-506 |
| Saddle Stitcher | SD-513 |
| Folding Unit | FD-504 |
| Creaser Unit | CR-101 |
| Trimmer Unit | TU-503 |
| Large Capacity Stacker | LS-507 |
| Large Capacity Stacker Handcart | LC-502 |
| Trimmer Unit | TU-510 |
| Creaser Unit | CR-102 |
| Trimmer Unit | TU-504 |
| Banner Unit | MK-764 |
| Job Separator | JS-507 |
| Creaser | CR-103 |
| Perforation Unit | PE-101 |
| Perforation Unit | PE-102 |
| Dust Box | MK-765 |
| Folding Unit | FD-503 |
| Perfect Binder | PB-503 |
| Output Tray | OT-512 |
| Output Tray | OT-511 |
| Mount Kit | MK-737 |
| Relay Unit | RU-510 |
| Relay Unit | RU-518m |
| Humidifier | HM-103 |
| Intelligent Quality Optimizer | IQ-501 |
| Relay Unit | RU-702 |
| Auto Inspection Unit | UK-301 |
| Inspection Enhancement Kit | UK-311 |
| Variable Data Inspection Kit | UK-312 |
| Video Interface Kit (Essential option for IQ-501) | VI-514 |
| Banner Tray Unit (Output) | MK-761 |

Electronic options

| | |
|---|---------|
| Image Controller (KM) | IC-609 |
| Upgrade Kit | UK-220 |
| Image Controller (Fiery) | IC-317 |
| Image Controller (Fiery) | IC-419 |
| Video Interface Kit (Essential option for IC-317/IC-419/UK-301) | VI-515 |
| Authentication Unit | AU-201S |