

TU-510e

TECHNICAL SPECIFICATIONS

RETHINK INLINE FINISHING

TU-510e

Basic function	2-side slit, 4-edge trim, 4-edge trim + 2-way slit
Media weight	50-400 g/m ² up to 487.7 mm, 128 – 300 g/m ² up to 1,300 mm*
Media size	Min 140 x 153 mm, max. 330.2 x 1,300* mm (900 mm duplex mode) *
Weight	272 kg / 328 kg with all options

* requires MK-764

JS-507 – Business Card Tray Kit

Basic function	Enables business card cutting with separate output tray
Standard finished size	50 x 85 mm to 56 x 92 mm
Standard number of cards	Trims 7 columns x 3 rows (21 cards per sheet)
Output capacity	420 Business Cards (depending on paper weight)

MK-764 – Banner Paper Kit

Basic function	Enables long-sheet feeding and page reversal during paper output
-----------------------	--

TU-504 – Center Slit Kit

Basic function	One- or two-line slitting	
Paper weight	128 to 300 g/m ²	
Media size before trimming	1-line slitting	Min 194 x 133 mm Max 330.2 x 487.7 mm
	2-line slitting	Min 271 x 133mm Max 330.2 x 487.7 mm
Media size after trimming	1-line slitting	Min. 85 x 133 mm Max. 161.1 x 487.7 mm
	2-line slitting	Min. 85 x 133 mm Max. 104.7 x 487.7 mm

CR-102 Creasing Kit

Basic function	Downward convex crease operation
Number of creases	1 to 5
Crease setting steps	0.1 mm
Minimum crease interval	1 mm



KONICA MINOLTA

Konica Minolta Business Solutions India Pvt. Ltd.

Building No: 8, Tower-C. 10th Floor, DLF Cyber City, Phase-2, Gurugram, Haryana-122002, India
Board No. +91-124-6652000 | URL: bt.konicaminolta.in | marcom@bin.konicaminolta.in

Connect with us : [in](#) [X](#) [f](#) [@](#)

For Demo Call: 1800-266-2525