





OPTIONS



Document converter pack LK-110v2

Trusted Platform Module activation LK-115v2

Antivirus LK-116





bizhub c4050i A4 Colour **Multifunctional Printers**

FINISHING FUNCTIONALITIES







Duplex

stapling (offline)

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

Print size/resolution	10.1" / 1024 x 600
System memory (standard/max)	5,120 MB
System hard drive	256 GB SSD (standard)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S); AppleTalk; Bonjour
Automatic document feeder (standard)	Up to 80 originals; A5–A4; 50–128 g/m²; Dualscan ADF
Paper input capacity (standard/max)	600 sheets / 1,600 sheets
Paper tray input (standard)	1x 500 sheets; A6–A4; Custom sizes; 60–210 g/m²
Paper tray input (optional)	1x 500 sheets; A4 ;60–90 g/m² 1x 500 sheets; A4 ;60–90 g/m²
Manual bypass	100 sheets; A6–A4; Custom sizes; 60–210 g/m²
Automatic duplexing	B5-A4; 60-210 g/m ²
Finishing modes (optional)	Group; Sort; Staple (offine)
Output capacity (standard)	Max. 250 sheets
Power consumption	220-240 V / 50/60 Hz; Less than 1.45 kW
System dimension (W x D x H)	420 x 528 x 572 mm (without options)
System weight	Approx. 39.0 kg (without options)

PRINTER SPECIFICATIONS

113
1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Windows 7 (32/64); Windows 8/8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.10 or later; Unix; Linux; Citrix
80 PCL Latin; 137 PostScript 3 Emulation Latin
AirPrint (iOS); Mopria (Android); Konica Minolta Mobile Print (iOS/Android/Windows 10 Mobile); Mobile Authentication and Pairing (iOS/Android) Optional: Google Cloud Print; WiFi Direct

SCANNER SPECIFICATI	01/13
Scan speed (mono/colour)	Up to 45/45 ipm in simplex Up to 90/90 ipm in duplex
Scan modes	Scan-to-email (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS; PPTX Optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/PPTX/XLSX
Scan destinations	2,100 (single + group); LDAP support

COPIER SPECIFICATIONS

Imaging technology	Laser
Toner technology	Simitri® HD polymerised toner
Copy/print speed A4 (mono/colour)	Up to 40/40 ppm, upto 33 33ppm
Autoduplex Speed A4 (mono/colour)	Up to 40/40 ppm, upto 33 33ppm
1" copy out time A4 (mono/colour)	4.8/5.4 sec., 5.6 6.3 sec.
Warm-up time	Approx. 13 sec. in mono; 15 sec. in color ²
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	A6–A4; Custom sizes
Magnification	25–400% in 0.1% steps; Auto-zooming

FAX SPECIFICATIONS

Fax standard	Super G3
Fax transmission	Analogue; i-Fax; Colour i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication); Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling

CVCTEM FEATURES

ISO 15408 HCD-PP Common Criteria (in evaluation); IP filtering and port blocking; SSL2; SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support; IEEE 8021. support; User authentication; Authentication log; Secure print; Kerberos; Hard drive overwrite; Hard drive data encryption (AES 256); Confidential fax receipt; Print user data encryption
Antivirus realtime scanning (Bitdefender®)
Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder); User function access definition
Biometric authentication (finger vein scanner); ID card authentication (ID card reader); Authentication by mobile device (Android/iOS)
Net Care Device Manager; Data Administrator; Box Operator; Web Connection; Print Status Notifier; Driver Packaging Utility; Log Management Utility



- ² Warm-up time may vary depending on the operating environment and usage
- All specifications refer to A4-size paper of 80 g/m2 quality.
- The support and availability of the listed specifications and functionalities vary depending on operating systems, applications and network protocols as well as network and system configurations.
- Some of the product illustrations contain optional accessories.
 Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.

 All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

Product appearance, configuration and/or specifications are subject to change without notice. This product is not available for some countries or regions. KONICA MINOLTA, symbol mark, Giving Shape to Ideas, AccurioLabel, AccurioPro, Simitri, S.E.A.D. and KONICA MINOLATA OPTIMIZED PRINT SERVICES are registered trademarks of KONICA MINOLTA, INC.
Windows and Windows Server are registered trademarks or trademarks of Microsoft Corporation in the U.S. and other countries.
Adobe and PostScript are registered trademarks of Adobe Systems Inc.
Mac OS is registered trademark or trademarks of their respective companies or organisations.

Please read and follow the Only operate using approximate the Only operate using a



From consulting, system design, to operations, Konica Minolta offers total support to optimise your office output environment.

http://www.bt.konicaminolta.in

⚠ Requirements for safe use

- Please read and follow the instruction manual to ensure safe operation.
- Only operate using appropriate power supply and voltage.
 Connecting the earth wire to an inappropriate place may cause explosion or electric shock. Please connect accordingly (Taiwan and the Philippines only).























