

# AccurioPress C84hc/C74hc General Specifications

Main Unit	C84hc	C74hc	
Type	Console type		
Colour support	Full colour		
Writing resolution	Equivalent to 3600 dpi x 2400 dpi		
Gradation	8 bit / 256 gradation		
Warm-up time	390 sec. or less		
Magnification	25 - 400%, in 0.1% steps		
Print speed full colour & monochrome	81 ppm (A4 Landscape) / 45 ppm (A3)	71 ppm (A4 Landscape) / 39 ppm (A3)	
First Copy/Printing Time (Color/Monochrome)	6.1 seconds or less/4.0 seconds or less		
Paper size	100 x 148 - 330.2 x 487.7 mm (up to 1,300 mm with optional Banner Kit)		
Paper weight	62 - 360 gsm		
Paper capacity	15,390 sheets (with main body standard tray + 3 paper feeding units (PF-707m Type C))		
Paper weight	12,000 sheets (with Large Capacity Stacker LS-507 x 2)		
Controller CPU	Intel Core i5-6500 3.2GHz <sup>1</sup>		
Power supply	AC 200V, 25A, 50Hz/60Hz (Voltage to ground 100V)		
Maximum Power Consumption	5,760W		
Main Unit Size (WxDxH mm)	Main unit	31.50 x 35.55 x 40.98 inches (800 x 903 x 1,041 mm)	
	(Recommended) configuration	84.65 x 35.55 x 58.19 inches (2,150 x 903 x 1,478 mm) (main unit + LU-202m + FS-532m)	
Main Unit Weight	Approx. 672.41 lb (305 kg)		
Maximum Print Area	12.72 x 18.90 inches (323 x 480 mm) (Banner sheet: 12.72 x 50.98 inches (323 x 1,295 mm))		
Compatible Paper weights	Main unit	16 to 68 lb (62 to 256 <sup>2</sup> g/m <sup>2</sup> )	
	Paper feed	PF-707m: 16 to 95 lb (62 to 360 g/m <sup>2</sup> ) MB-508: 16 to 81 lb (62 to 300 g/m <sup>2</sup> )	
	Paper output	Straight paper output: 16 to 95 lb (62 to 360 g/m <sup>2</sup> ) Reverse double-sided output: 16 to 95 lb (62 to 360 g/m <sup>2</sup> )	
	Banner paper	MK-760/MK-761: 34 to 68 lb (128 to 256 g/m <sup>2</sup> ) (up to 51.18 inches (1,300 mm) length) LU-202XLm: 34 to 68 lb (128 to 256 g/m <sup>2</sup> ) (18.85 to 30.00 inches (478.8 to 762 mm) length)	
Paper Feed Capacity (21 lb (80 g/m <sup>2</sup> sheet))	PF-707m: 3-level tray, air suction system Top level/Middle level: 1,390 sheets each, Bottom level: 1,850 sheets 15,390 sheets (Main unit tray, with 3 PF units connected)		
Paper output capacity (21 lb (80 g/m <sup>2</sup> sheet))	RU-518m (Sub Tray) 100 sheets (stacking height: 20 mm)		
Copy Speed	Single side A4	81 ppm or 4,399 sides or more/hour	71 ppm or 3,848 sides or more/hour
	Simplex A3	45 ppm or 2,404 pph	39 ppm/ 2,074 pph
Compatible Controllers	IC-609 (KM), IC-317 ver.3.0 (Fiery), IC-419 ver.3.0 (Fiery)		

\*1: In the case of Image Controller IC-609

\*2: For 58 to 68 lb (217 to 256 g/m<sup>2</sup>), only papers that are at least 8.27 to 11 inches (210 x 279.4 mm)

## Other options

Working Table	WT-511
Envelope Fusing Unit	EF-107
Dehumidifier Heater	HT-511
Status indicator light	MK-744C
Intelligent Media Sensor	IM-101

- All specifications refer to A4-size paper of 80 gsm quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

## Paper feeding options

Paper Feeder Unit	PF-602m
Dehumidifier Heater (Europa)	HT-504
Dehumidifier Heater (Japan/North America)	HT-505
Paper Feed Unit	PF-707m
Dehumidifier Heater	HT-506
Feed Adjuster	FA-502
Multi Bypass Tray	MB-508
Large Capacity Unit	LU-202m
Large Capacity Unit	LU-202XLm
Dehumidifier Heater	HT-503
Dehumidifier Heater	HT-515
Mount Kit	MK-746
Multi Bypass Tray	MB-509
Banner Tray Unit (Input)	MK-760

## Paper ejection options

Finisher	FS-532m
Saddle Stitcher	SD-510
Punch Unit	PK-525
Mount Kit	MK-732
Post Inserter	PI-502
Saddle Stitcher	SD-506
Saddle Stitcher	SD-513
Folding Unit	FD-504
Creaser Unit	CR-101
Trimmer Unit	TU-503
Large Capacity Stacker	LS-507
Large Capacity Stacker Handcart	LC-502
Trimmer Unit	TU-510
Creaser Unit	CR-102
Trimmer Unit	TU-504
Banner Unit	MK-764
Job Separator	JS-507
Creaser	CR-103
Perforation Unit	PE-101
Perforation Unit	PE-102
Dust Box	MK-765
Folding Unit	FD-503
Perfect Binder	PB-503
Output Tray	OT-512
Output Tray	OT-511
Mount Kit	MK-737
Relay Unit	RU-510
Relay Unit	RU-518m
Humidifier	HM-103
Intelligent Quality Optimizer	IQ-501
Relay Unit	RU-702
Auto Inspection Unit	UK-301
Inspection Enhancement Kit	UK-311
Variable Data Inspection Kit	UK-312
Video Interface Kit (Essential option for IQ-501)	VI-514
Banner Tray Unit (Output)	MK-761

## Electronic options

Image Controller (KM)	IC-609
Upgrade Kit	UK-220
Image Controller (Fiery)	IC-317
Image Controller (Fiery)	IC-419
Video Interface Kit (Essential option for IC-317/IC-419/UK-301)	VI-515
Authentication Unit	AU-201S



Konica Minolta Business Solutions India Pvt. Ltd.

Building No: 8, Tower-C, 10th Floor, DLF Cyber City, Phase-2, Gurugram, Haryana-122002, India | Board No. +91-124-6652000

URL: www.konicaminolta.in | marcom@bin.konicaminolta.in

Connect with us: [in](#) [x](#) [f](#) [o](#)