

VERSATILE PERFORMANCE IN COLOUR & MONO















































bizhub c227



The simplicity and usability to fit in any working environment



The bizhub C227 adopts easy and intuitive INFO-Palette design with smart user interface. You get the same user experience through seamless operation across the PCs, tablets or smartphones.



INFO-Palette

Lighter and compact MFP body

The newly developed MFP offers compact and lightweight body so as to fit almost in any type of working space.

New 7 inch operation panel

The new 7 inch operation panel provides best in class multi-touch sensitivity, user friendly interface and intuitive operability. User can register up to 9 functions with the combination of hard and soft menu keys mounted on the panel.

The screen display function can be enlarged and screen display colour can be reversed for



Soft menu keys will appear by tapping ont the screen tab.

Widgets function

The new bizhub C227 comes with embedded widget application where users can install and execute within the MFP operation panel. Text boxes, icons or GIF animations can be configured and used for internal communication, messages and rules.



Print from anywhere, anytime with the most advanced wireless, mobile and cloud technology

To connect with Android devices

The operation panel is equipped with newly embedded Mobile Touch Area to support NFC (Near Field Communication) connection for Android devices. Pairing can be performed, through Page Scope Mobile (PSM), by touching the area with Android device. First select the files on PSM and then touch the device to the operation panel to perform print or scan

- *1 NFC connection requires Android OS 4.4 or highest to be installed.
- *2 Wireless LAN environment is required to perform touch to print & scan



To connect with iOS devices

For the iOS devices, you can search and register nearby bizhub into the PageScope Mobile (PSM)³ via Bluetooth LE (BLE)⁴ technology. iOS devices can also be used to log-into bizhub via BLE connection. Selected files on PSM can be printed 5 directly or scan 5 files to iOS devices.

- *3 PageScope Mobile for iPhone / iPad version 5.0 or higher is required.
 *4 Otional Device Connection I/F Kit EK-609 is required.
- *5 Wireless LAN environment is required to perform print and scan

Wireless LAN (AP mode) support

Make your bizhub wireless LAN Access Point's to wirelessly connect mobile devices. Devices thus will not only able to connect directly with bizhub but are also securely separated from existing LANS

PageScope Mobile¹³ will enable more convenience as wireless set up can be completed between a mobile device and bizhub by reading the QR code that is displayed on the machine panel

*6 Optional Upgrade Kit UK-212 and Device Connection I/F Kit EK-608 or EK-609 are required.

QR code display screen





Wireless LAN (AP mode) connection image

In AP mode (base unit), simultaneous connections can be made with up to 5 devices.

Standard web browser

The multi-touch UI in the operational panel can be used to display and print webpage contents. Printing of portions of PDF files or maps directly from the websites are more convenient now.

To connect instantly without print drivers to the industry standard mobile technologies

Apple's standard printing system is compatible with iOS 4.2 and Mac OS 10.7 or later. A compatible printer on your wireless LAN can be used.




Mopria Print Service

Wireless printing technology established by Mopria Alliance. It allows you to print from devices installed with Android 4.4 or later.



Google Cloud Print

A cloud print service provided by Google. You can print from any location via the internet regardless of OS or device type.





Konica Minolta Print Service

Print directly to bizhub via a wireless LAN from all apps that supports Android's print function.



PageScope Mobile

Konica Minolta's proprietary mobile print application allows usage of wide range of bizhub functions such as duplex print, security print, staple and punch.



Flexible and advanced security features to protect valuable information



Authentication on the MFP main unit

User can perform authentication directly on the main unit. Access control can be set up for functions like print, scan, copy and fax

*1 Fax feature requires optional Fax Kit Fk-513 & HDD will be needed if MFP does not equip the HDD as standard

IC card authentication

Users can authenticate with various types of IC card³. The authentication method complies with SSFC (Shared Security Formats Cooperation). Besides the IC Card, users can authenticate with Android devices with equipped NFC antenna.



- *2 Optional Authentication Unit AU-201S and Device Connection I/F Kit EK-608 or EK-609 are required.
- *3 Compliant non-contact IC cards include FeliCa (Idm), SSFC, FCF, FCF (campus), FeliCa Private, and MIFARE (UID), *4 Requires Android 4.4 or later that supports HCE (Host Card Emulation) or PageScope Mobile for Android v4.1 or later

Biometric authentication

Scans the veins on the finger as the biometric data which offers very high-level security and is easy to implement 4.



*4 Optional Biometric Authentication Unit AU-102, Working Table WT-506 and Device Connection I/F Kit EK-608 or FK-609 are required

TPM (Trusted Platform Module)

TPM (Trusted Platform Module) is a security chip which encrypts and decrypts confidential data. The information is encrypted and stored in dedicated storage area in the chip to avoid unauthorized reading.

* Optional i-Option LK-115 v2 is required.

ID & Print

To restrict the outputs to specific user or print confidential documents, user can set a password before executing the print. The print data will be stored in the HDD of the MFP and will not be printed until the same password is entered on the MFP.




Environmental contribution is always the top priority

Top class power consumption and TEC value in its class

The MFP's CPU power is set to turn off during sleep mode. This results in a best-in-class 0.5 W power consumption ratio (during sleep mode). The TEC value has also been reduced approximately by 67-68%. CO_2 emission from the MFP is drastically reduced.

SYSTEM

- Upgrade kit UK-211
- 2 GB memory
- Upgrade kit UK-212
 Wireless LAN kit
 * EK-608 or EK-609 is required.
- Device Connection I/F Kit EK-608 USB hub kit / Voice guidance
- Device Connection I/F Kit EK-609 Bluetooth LE / Voice guidance
- bizhub Connector S-1/G-1/E-1
- Keypad KP-101



Select One of the options may be selected (not mandatory)

Must Select One of the options must be selected (mandatory)

bizhubC227 Printer Specifications

	•	bizhub C227
Туре		Embedded
		ARM Cortex-A7 Dual-core 1.2GHz
Memory		2 GB (2,048 MB)
Print Speed		22 ppm
HDD		250 GB (Optional, shared with the copier)
Print Resolution		1,800 dpi (equivalent) × 600 dpi
PDL		PCL5e/c, PCL 6, PostScript 3 Emulation, XPS, BMLinkS
Protocol		TCP/IP (LPD, Raw, SMB, IPP), IPX/SPX (NDS support), AppleTalk
Support OS		Windows Vista*1 / 7*1 / 8*1 / 8.1*1 / 10*1
		Windows Server 2008*1 / 2008 R2 / 2012 / 2012 R2
		Mac OS X (10.6 / 10.7 / 10.8 / 10.9 / 10.10 / 10.11)
		Linux
Fonts	PCL	80 Roman fonts
	PS	137 Roman Type1 fonts
Interface		Ethernet (10BASE-T/100BASE-TX/1000BASE-T),
		USB 1.1, USB 2.0, IEEE 802.11 b/g/n*2

- *1 Supports the 32-bit (x86) or 64-bit (x64) environment

Scanner Specifications

Type		Full-Colour Scanner
Interface		Ethernet (10BASE-T/100BASE-TX/1000BASE-T),
		USB 1.1, USB 2.0, IEEE 802.11 b/g/n*1
Driver		TWAIN Driver, HDD TWAIN Driver
Protocol		TCP/IP (FTP, SMB, SMTP, WebDAV) (IPv4/IPv6)
Scanning Speed(Colour/B&W)		45 opm*2
(300 dpi, A4, Simplex)		
Scanning Size		Max. A3 (11" × 17")
Output Format		TIFF, JPEG, PDF, Compact PDF, XPS, Compact XPS, OOXML (pptx, xlsx*1, docx*1), Searchable PDF*1, PDF/A*1, Linearised PDF*1
Scanning Resolution	Push	200 dpi / 300 dpi / 400 dpi / 600 dpi
	Pull	100 dpi / 200 dpi / 300 dpi / 400 dpi / 600 dpi
Main Functions		Scan to E-Mail, Scan to FTP, Scan to BOX (HDD), Scan to PC (SMB), Network TWAIN, Scan to WebDAV, Scan to USB, Scan to Scan Server, Scan to Me, Scan to Home, Scan to Web Service (WSD-Scan), Device Profile for Web Services (DPWS)
Other Functions		Multi-Method Send, Authentication at the time of E-Mail send (SMTP authentication, POP before SMTP), S/MIME, Annotation

- *2 When using the Reverse Automatic Document Feeder DF-628.
- *3 Supports the 32-bit (x86) or 64-bit (x64) environment

Copier / General Specifications

Type		Desktop Full Colour A3 Multifunctional Printer	
Colour Support		Full colour	
Copy Resolution	Scan	Main: 600 dpi × Sub: 600 dpi	
	Print	1,800 dpi (equivalent) × 600 dpi	
Gradation		256	
Memory Capacity (Std./Max.)	2 GB	
HDD		250 GB (optional)	
Original Type		Sheets, Books, Objects	
Max. Original Size		A3	
Output Size	Main unit	A3 to A5	
	Bypass Tray	A3 to A5, B6 ⁺¹ , A6 ⁺¹ , Postcard, Envelope ⁺² , Tab paper,Banner paper (Width: 210 mm to 297 mm, Length: 432 mm to 1,200 mm)* ³	
Warm-Up Time*4 (23°C, std. voltage)		Colour/B&W: 20 sec. or less	
* The time required to start printing when both the main power and sub-power switches are turned from OFF to ON.			
* The time required to start printing when the main power switch is ON and the sub-power switch is turned from OFF to ON.		Colour/B&W: 20 sec. or less	
First Copy Out	Colour	8.4 sec. or less	
Time*5	B/W	6.8 sec. or less	
Copy Speed (Colou	r/B&W, A4)	22 ppm	
Сору	Fixed Same Magnification	1: 1±0.5% or less	
Magnification	Scaling Up	1: 1.154/1.224/1.414/2.000	
	Scaling Down	1: 0.866/0.816/0.707/0.500	
	Preset	3 types	
	Zoom	25 to 400% (in 0.1% increments)	
	Lengthwise Crosswise Individual Settings	25 to 400% (in 0.1% increments)	
Paper Capacity (80 g/m²)	Tray 1	500 sheets	
	Tray 2	500 sheets	
	Multiple Bypass Tray	100 sheets	
Max. Paper Capacity (80 g/m²)*6		3,600 sheets	
Paper Weight	Tray 1 / 2	60 to 256 g/m	
	Multiple BypassTray	60 to 256 g/m	

Auto Duplex	Paper Size	A3 to A5, B6°1, A6°1, Postcard	
	Paper Weight	60 to 209 g/m ²	
Power Requirements		AC220 to 240 V 8 A (50 to 60 Hz)	
Max. Power Consumption		1.58 kW or less	
Dimensions $[W] \times [D] \times [H]$		585 × 660 × 787 mm (23-1/16" × 26" × 31")	
Weight		Approx. 72 kg (158-3/4 lb)	
Space Requirements [W] × [D]*7		899 × 1,090 mm (35-1/2" × 45-15/16")	

- *1 Short edge feed .

*7 Without options, with paper trays pulled out, and multiple bypass tray, auxiliary tray and ADF opened.

Fax Kit FK-513* (*Optional)

Communication	Super G3
Compatible Lines	Public Switch Telephone Network, Private Branch Exchange, Fax Communication Line
Line Density	Ultra Fine: 600 dpi 600 dpi
	Super Fine: 16 dot/mm 15.4 line/mm, 400 dpi 400 dpi
	Fine: 8 dot/mm 7.7 line/mm, 200 dpi 200 dpi
	Normal: 8 dot/mm 3.85 line/mm
Modem Speed	2.4 to 33.6 kbps
Compression	MH/MR/MMR/JBIG
Sending Paper Size	Max. A3 (Long Length Support: Max.1,000 mm)
Recording Paper Size	Max. A3 (Long Length Max. 1,000 mm following the page division)
Transmission Speed	Less than 2 sec. (A4, V.34, 33.6 kbps, JBIG)
Memory	Shared with the copier
Number of Abbr. Dials	2,000
Number of Program Dials	400
Number of Group Dials	100
Sequential Multiple Station Transmission	Max. 600

^{*}Optional HDD HD-522 required

Internet Fax (*Optional)

Protocol	TX: SMTP, RX: POP3, TCP/IP Simple mode
Connection Mode	Full-Mode
Sending Paper Size	A3, B4, A4
Recording Paper Size	Max. A3
Resolution	B/W: 200 × 100 dpi, 200 × 200 dpi, 400 × 400 dpi, 600 × 600 dpi
	Colour: 200 × 200 dpi, 400 × 400 dpi, 600 × 600 dpi
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T)
Colour	Support Colour Internet Fax
Format	B/W: TIFF-F Colour: TIFF (Conforms to RFC3949 Profile-C)

IP Address Fax (*Optional)

Protocol Transmission	TCP/IP, SMTP
Sending Paper Size	A3, B4, A4
Resolution	200 × 200 dpi, 400 × 400 dpi, 600 × 600 dpi
Format	B/W: TIFF-F, TIFF-S
	Colour: TIFE PDF

^{*}Optional Fax kit FK-513 & HDD-522 is required

Reverse Automatic Document Feeder DF-628 (*Optional)

Type		Circulatory duplex system	
Support Paper Size		Max. A3 (Fax mode: Max. 1,000 mm)	
Mixed Size		Support	
Original Set		Centre guide	
Support Paper Weight		Simplex: 35 to 128 g/m²	
		Duplex/Mixed Original: 50 to 128 g/m²	
Paper Capacity		Max. 130 sheets (68 g/m²)	
Productivity	Simplex	Colour/B&W: 45 opm (300 dpi), 36 opm (600 dpi)	
(A4)	Duplex	Colour/B&W: 22 opm (300 dpi), 17 opm (600 dpi)	
Power Requirements		Supplied from the MFP main body	
Dimensions $[W] \times [D] \times [H]$		585 × 504 × 127 mm (23" × 19-3/4" × 5")	
Weight		Approx. 9 kg (19-3/4lb)	

For more information please visit the bizhub Web site at http://bt.konicaminolta.in/bizhub-c227-product-overview/

Product Appearance, Configuration And/or Specifications Are Subject To Change Without Notice.

KONICA MINOLTA, the KONICA MINOLTA logo and symbol mark, "Giving Shape to Ideas", bizhub, bizhub PRO, bizhub PRESS, magicolor, PagePro, PageScope, Simitri, Simitri HD+, Simitri with Biomass, Emperon, S.E.A.D., S.E.A.D.II, Printgroove and Konica Minolta Optimised Print Services and their respective logos are registered trademarks or trademarks of KONICA MINOLTA, INC. Evernote is a registered trademark or trademark of Evernote Corporation. SharePoint is a registered trademark or trademark of Microsoft Corporation in the U.S. and other countries.

All other brands and product names are registered trademarks or trademarks of their respective companies or organisations.







Ecology & Environment

 $KONICA\,MINOLTA\,products\,are\,designed\,with\,the\,environment\,in\,mind.$

- Energy Star
- RoHS Compliance
- WEEE Compliance Eco-friendly Toners





- Please read and follow the instruction manual to ensure safe operation.
 - Only operate using appropriate power supply and voltage
- $\bullet \textbf{Connecting the earth wire to an inappropriate place may cause explosion or electric shock. Please connect accordingly.}\\$

Contact Point:

For more information: SMS "KM OFFICE" send to 52424 or Call: 1-800-266-2525 Konica Minolta Business Solutions India Pvt. Ltd.: 10th Floor, Building No.8, Tower C, DLF Cyber City, Phase II Gurgaon, Haryana - 122002, India. Board No. +91-124 6652000. URL: www.konicaminolta.in, marcom@bin.konicaminolta.in | Konica Minolta Inc., Tokyo, Japan.