

| IQ-501 system | | |
|------------------------|---|---|
| Type | Console | |
| Product Category | Automatic image reader | |
| Configuration | Colour | IQ-501 + VI -511 (image processor, basic option) |
| | BW | IQ-501 + VI -512 (image processor, basic option) |
| Compatible Presses | Colour | AccurioPress C6100, C6085, AccurioPress C3080, C3080P, C3070, C3070P, C83hc |
| | BW | AccurioPress 6136, 6136P, 6120 |
| Functions | Single pass duplex in-line scanner + spectrophotometer • In-line scanner 1: Rear side • In-line scanner 2: Front side • Spectrophotometer: Colourimetry on the front surface (spectral reflectivity) | |
| Print Speed | Up to 150 ppm (A4, Letter (8.5 x 11 in.)) (depends on printer specifications) | |
| Scan width | Max. 350 mm (main-scan direction) | |
| Compatible Format | 95 x 139 to 331 x 488 mm (compatible with banner format) | |
| Compatible Grammage | 40 to 400 gsm (depends on the grammage of the connected printer) | |
| Incompatible Media | Embossed paper, index paper, OHP | |
| Power Source | 100 to 240VAC 50/60Hz | |
| Power Consumption | 700W or less (including latter connected options) | |
| Dimensions (W x D x H) | 663 x 696 x 1,020 mm | |
| Weight | Approx. 184 kg | |

Real-time Gradation and Front-to-Back Registration Adjustment

| Compatible Paper Sizes | |
|------------------------|--|
| Standard sizes | SRA3, SRA4L 13 × 19 ins., 12 × 18 ins. Or paper that has some room in the sub-scanning direction |
| Custom sizes | Sub-scanning direction 225 mm or more |

Simultaneous Automatic Adjustment *Default Setting

| | Adjustment Time | Output Sheet Count |
|---------------------------------------|-------------------------|--------------------|
| Automatic gamma adjustment* | 2 minutes or less | 0 |
| Density balance adjustment | 1 minute or less | 2 sheets |
| Automatic maximum density adjustment* | 6 minutes or less | 4 sheets |
| Output paper density adjustment* | 1 minute or less | 2 sheets |
| Exact colour | 5 minutes or less (TBD) | 3-5 sheets |